



# Rembrandt Piccolo 1,2 kW MK2

The NEW technology in discharge Daylight Fixtures

MOD. 2512



**WEIGHT:**

- 9 Kg.

**CONSTRUCTION:**

- Fixture housing in STAINLESS STEEL (INOX).

**FINISHING:**

- SAND BLASTED AND CHEMICALLY TREATED MATT STAINLESS STEEL (INOX).

**PROTECTION FACTOR:**

- IP 23, allowing the use of the fixture during moderate rain.

**DISCHARGE LAMP TYPES:**

- Single ended Hot Re-strike 1,2 kW discharge lamps

**LAMP HOLDER POWER**

- QUICK ACTION LEVER TYPE G38 BI-POST FOR DISCHARGE LAMPS

**HIGH VOLTAGE ELECTRONIC IGNITER,**

- assembled on the lamp carriage, eliminating the need of movable HIGH VOLTAGE internal cables.
- SILENT operation of the IGNITER also in FLICKER FREE mode.

**PHOTOMETRIC DATA REMBRANDT Piccolo 1200W**

Values measured with: MSR 1200 HR, 150 mm. Dia. Fresnel Lens

FEET

TYPICAL DISTANCES | 20' | 30' | 40' | 50'

LIGHT CENTER VALUES	Candle Power	FOOTCANDLES			
SPOT	464,275	1,161	516	290	186
FLOOD	66,150	165	74	41	26

F.C. at any distance = CANDLE POWER : [Distance (in ft)]<sup>2</sup>

BEAM ANGLE (50% OF CENTER VALUE)	BEAM DIAMETER in feet				
SPOT	9°	3.1'	4.7'	6.3'	7.9'
FLOOD	54.9°	20.8'	31.2'	41.6'	51.9'

